

| WSSS AD 2.13 DECLARED DISTANCES | | | | | | |
|--|--------------------------------|-----------------|-----------------|-----------------|----------------|----------------------------------|
| <i>RWY Designator</i> | <i>Intersection Departures</i> | <i>TORA (m)</i> | <i>TODA (m)</i> | <i>ASDA (m)</i> | <i>LDA (m)</i> | <i>Remarks</i> |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 20R | Not applicable | 4000 | 4270 | 4060 | 3260 | Thr displaced by 740m southwards |
| | W2 | 3850 | 4120 | 3910 | Not applicable | |
| | W3 | 3050 | 3320 | 3110 | Not applicable | |
| | W4 | 2600 | 2870 | 2660 | Not applicable | |
| | W5 | 2150 | 2420 | 2210 | Not applicable | |
| 02L | Not applicable | 4000 | 4270 | 4060 | 4000 | Nil |
| | W8 | 3850 | 4120 | 3910 | Not applicable | |
| | W7 | 3050 | 3320 | 3110 | Not applicable | |
| | W6 | 2600 | 2870 | 2660 | Not applicable | |
| 20C | Not applicable | 4000 | 4270 | 4060 | 4000 | Nil |
| | E2 | 3850 | 4120 | 3910 | Not applicable | |
| | E3 | 3425 | 3695 | 3485 | Not applicable | |
| | E4 | 2750 | 3020 | 2810 | Not applicable | |
| | E5 | 2250 | 2520 | 2310 | Not applicable | |
| 02C | Not applicable | 4000 | 4270 | 4060 | 4000 | Nil |
| | E10 | 3850 | 4120 | 3910 | Not applicable | |
| | E9 | 3345 | 3615 | 3405 | Not applicable | |
| | E8 | 3205 | 3475 | 3265 | Not applicable | |
| | E7 | 2555 | 2825 | 2615 | Not applicable | |
| | E6 | 2105 | 2375 | 2165 | Not applicable | |
| 02R | Not applicable | 2750 | 2750 | 2900 | 2750 | Nil |
| 20L | Not applicable | 2750 | 2750 | 2900 | 2750 | |

Note: Intersection departures are allowed subject to the following:
 (a) initiated by pilot and approved by ATC, traffic permitting.
 (b) ATC is able to keep aircraft visual at all times